

Model 290

Sanitary Pressure Transducer

The Model 290 is Setra's highest accuracy solution for measuring gauge and compound pressure ranges in sanitary processing applications. Unlike competitive transducers which use an oil filled design, the 316L stainless steel sensor is designed to operate without the need for an intermediary liquid within the sensor. The design of the 290 negates clamp effect making installation and service faster and easier than the competition. Its small footprint and accuracy ($\pm 0.2\%$ FS) covers a wide range of pressure ranges that meet both 3A certification and withstand CIP/SIP environmental conditions, making it ideal for a variety of applications.

Robust Non-Liquid Filled Sensor

The Model 290 sanitary pressure transducer uses an air variable capacitance sensor. This sensor design eliminates chance of "product" contamination, position effect and thermal transients when compared to liquid filled sensors. The diaphragm is able to withstand pressure down to full vacuum for worry free operation during tank and piping evacuation cycles.

Negligible Clamping Effect

The process interface of the 290 negates the effect of clamping pressure on the output signal of the sensor. This design allows the sensor to be delivered in a small footprint with the diaphragm closely mounted to the process media which ensures the most accurate measurements.

Flexibility in Application

The Model 290 is the most versatile sanitary pressure transducer on the market. Its design allows full scale tank level measurements as low as 27.7" WC with an accuracy of 0.027" and up to 1000 PSI for process lines. The 316L wetted components meet 3A requirements for food and beverage industry applications; its optional 20Ra finish make it the ideal solution for use in Biotech applications.



- Eliminates Process Contamination Risk
- 316L SS For Harsh Environments
- Meets 3A Sanitary Standards

Model 290 Features:

- High Accuracy: $\pm 0.2\%$ FS
- Robust Non-Liquid Filled Capacitive Sensor
- Negligible Clamping Effect for Easy Installation
- Designed for Clean-In-Place (CIP) and Sterilize-In-Place (SIP) Installations
- 1.5" and 2" Tri-Clover Fittings
- High Overpressure Protection
- Not Sensitive to Thermal Shock

Applications:

- Food Processing
- Dairy and Beverage Processing
- Pharmaceutical Processing
- Liquid Level Control
- Sanitary Pipelines

Model 290

Sanitary Pressure Transducer



ORDERING INFORMATION

2 9 0 1 - - - - - 1 1 - - - - -

| Model | Range | | Units | Pressure Type | | Fitting | Output | Termination | Accuracy | Options ² |
|------------|---------------------|-------------------------|--------|-------------------------|----------------|-------------------|------------|--------------|-------------|-----------------------|
| 2901 = 290 | 2" Tri-Clover (PSI) | 1 1/2" Tri-Clover (PSI) | p PSI | G Gauge | T ₆ | 1 1/2" Tri-Clover | 11 4-20 mA | 15 15' Cable | 3 ± 0.2% FS | N None |
| | 001 0-1 | 030 0-30 | M mBAR | C ₁ Compound | T ₈ | 2" Tri-Clover | | 25 25' Cable | T ± 0.1% FS | L Etched SS Tags |
| | 002 0-2 | 045* 0-45 | | | | | | 30 30' Cable | | R 20 Ra Sensor Finish |
| | 005 0-5 | 060 0-60 | | | | | | | | |
| | 010 0-10 | 100 0-100 | | | | | | | | |
| | 015 0-15 | 150 0-150 | | | | | | | | |
| | 030 0-30 | 300 0-300 | | | | | | | | |
| | 060 0-60 | 500 0-500 | | | | | | | | |
| | 100 0-100 | 10C 0-1000 | | | | | | | | |
| | 150 0-150 | | | | | | | | | |


¹ -14.7 to X psi, -1000 to X mBAR
² Both boxes must be filled in alphabetical order:
- If No options: N + N
- If 1 option: Option Code + N
- If 2 options: Option Code + Option Code

Proof Pressure: The maximum pressure that may be applied without changing performance beyond specifications (<±0.5% FS zero shift).
Burst Pressure: The maximum pressure that may be applied to the positive pressure port without rupturing the sensing element.


Example: Part No. 2901001PGT811153N = Model 290, 2" Tri-Clover 0 to 1 PSI, Gauge Pressure, 2" Tri-Clover Fitting, 4 to 20 mA Output, 15' Cable Termination, ± 0.2% FS Accuracy.

DIMENSIONS

1 1/2" Tri-Clover Sanitary Fitting
Diaphragm Material: 316SS



2" Tri-Clover Sanitary Fitting
Diaphragm Material: 316LSS



PROOF PRESSURE

| Pressure Ranges 2" Tri-Clover | | | | | Pressure Ranges 1 1/2" Tri-Clover | | |
|-------------------------------|-------------|----------------------|------------|------------|-----------------------------------|------------|------------|
| PSIG | Range mb | in. H ₂ O | Proof PSIG | Burst PSIG | Range PSIG | Proof PSIG | Burst PSIG |
| 1 | 100 | 27.7 | 50 | 100 | 30 | 1000 | 1200 |
| 2 | 160 | 55.4 | 75 | 150 | 60 | 1000 | 1200 |
| 5 | 400 | 138.4 | 150 | 200 | 100 | 1000 | 1200 |
| 10 | 600 | 276.8 | 150 | 200 | 150 | 1000 | 1200 |
| 15 | 1000 | 415.2 | 150 | 200 | 300 | 1000 | 1200 |
| 30 | | 830.4 | 150 | 300 | 500 | 1000 | 1500 |
| 60 | | 1660.8 | 180 | 400 | 1000 | 1250 | 2400 |
| 100 | | 2768 | 200 | 400 | -14.7 to 15 | 1000 | 1200 |
| 150 | | 4152 | 225 | 400 | -14.7 to 45 | 1000 | 1200 |
| -14.7 to 15 | -407 to 415 | 150 | 300 | | | | |

GENERAL SPECIFICATIONS

| Performance Data | | | Electrical Data | |
|---|--|--|--|--|
| | 2" Tri-Clover Sanitary Fitting | 1.5" Tri-Clover Sanitary Fitting | Circuit | 2-Wire |
| Accuracy RSS ¹ (at constant temp) | ±0.20% FS | ±0.20% FS | Output ³ | 4 to 20 mA ⁴ |
| Non-Linearity (BFSL) | ±0.17% FS | ±0.15% FS | Zero/Span, Adjustment | ± 0.5 mA |
| Hysteresis | 0.10% FS | 0.12% FS | External Load | 0 to 800 ohms |
| Non-Repeatability | 0.025% FS | 0.10% FS | Min. Supply Voltage (VDC) | 12 + 0.02 x resistance of receiver plus line |
| Thermal Effect ² | | | Max. Supply Voltage (VDC) | 30 + .004 x resistance of receiver plus line |
| Compensated Range F ³ (°C) | +20 to +180 (-7 to +82) | +20 to +180 (-7 to +82) | Environmental Data | |
| Zero/Span Shift %FS/100°F (%FS/50°C) | 2.0 (1.8) | 2.0 (1.8) | Operating Temperature°F (°C) ⁵ | -40 to +260 (-40 to +125) |
| Response Time | 10 milliseconds | 10 milliseconds | Storage Temperature°F (°C) | -65 to +260 (-55 to +125) |
| EMI/RFI Effect | < 1.0% output shift; 10V/M, 10-300 MHz | < 1.0% output shift; 10V/M, 10-300 MHz | Vibration | 10g, 50-1000Hz |
| Clamping Effect, Zero/Span Shift | ±0.15% FS | ±0.25% FS | Acceleration ⁶ | 10g maximum |
| Maximum Vacuum (without affecting specifications) | Half on ranges ≤15 PSI | Full on ranges ≥ 30 PSI | Shock | 50g operating |
| Physical Description | | | Thermal Shock°F (°C) | 0 to +257 (0 to +125) negligible shift |
| Zero/Span Adjustments | Top Access Through Seal Screws | | Approvals | |
| Case | Stainless Steel | | CE | |
| Electrical Connection | 1/2 NPT" Conduit Fitting & Strain Relief w/ 15' Shielded Cable | | Note: Setra quality standards are based on ANSI-Z540-1. The calibration of this product is NIST traceable. | |
| Pressure Fitting | 2" or 1 1/2" Tri-Clover Sanitary Fitting | | ¹ RSS of Non-Linearity, Non-Repeatability and Hysteresis. | |
| Sanitary | Meets 3-A Sanitary Standard (74-02) | | ² Units calibrated at nominal 70°F. Maximum thermal error is computed from this datum. Variations in the power supply voltage cause less than 0.005 mA change in the transmitter's current output, per volt change in the power supply. Reverse excitation will not damage circuit. | |
| Vent | Through Cable | | ³ Calibrated at factory with a 24 VDC loop supply voltage and a 250 ohm load. | |
| Weight (Approx.) | 8 Ounces | | ⁴ Zero output factory set to within ±0.08mA. | |
| | | | ⁵ Span (Full Scale) output factory set to within ±0.16mA. | |
| | | | ⁶ Operating temperature limits of the electronics only. Pressure media temperatures may be considerably higher or lower. | |
| | | | ⁷ shift in output reading at <0.05% FS/g; pressure port axis only. | |